

CIVIA PARKWAY 2.0 FRAMESHEET

Civia offers stylish, comfortable, affordable bikes that allow people to discover the joy just around the corner. We believe that riding a bike helps you see the world in a new way, that some of life's best things are found right outside your front door, and that life is more than getting from one place to another. Thanks for buying a Civia.

⚠WARNING: CYCLING CAN BE DANGEROUS. BICYCLE PRODUCTS SHOULD BE INSTALLED AND SERVICED BY A PROFESSIONAL MECHANIC. NEVER MODIFY YOUR BICYCLE OR ACCESSORIES. READ AND FOLLOW ALL PRODUCT INSTRUCTIONS AND WARNINGS INCLUDING INFORMATION ON THE MANUFACTURER'S WEBSITE. INSPECT YOUR BICYCLE BEFORE EVERY RIDE. ALWAYS WEAR A HELMET.

Additional Product and Safety instructions can be found at www.civiacycles.com/safety

RETAILER: This framesheet MUST BE provided to the end user.

INTENDED USE



CONDITION 1 CITY TREKKING

Our bikes are designed for riding on a paved surface where the tires are always on the ground.

GEOMETRY CHART

| Size | XS/SM | MD/LG |
|-------------------------------|--------------|--------------|
| A. Top Tube Effective | 550mm | 580mm |
| B. Seat Tube C-T | 450mm | 500mm |
| C. Head Tube Angle | 69.0° | 69.0° |
| D. Seat Tube Angle | 69.0° | 69.0° |
| E. Bottom Bracket Drop | 50mm | 50mm |
| F. Chainstay Length | 493mm | 493mm |
| G. Head Tube Length | 185mm | 220mm |
| H. Fork Length | 409mm | 409mm |
| I. Fork Offset | 45mm | 45mm |
| J. Wheelbase | 1066mm | 1096mm |
| K. Stack | 591mm | 624mm |
| L. Reach | 323mm | 341mm |
| M. Wheel Diameter | 658 (26x2.0) | 658 (26x2.0) |
| N. Stand Over | 657mm | 647mm |

* Standover is measured 50mm in front of the bottom bracket center and using a 26 x 2.0" tire measuring 658mm in diameter

GENERAL SPECIFICATIONS & COMPATIBILITY

| Frameset | |
|------------------------|---|
| Frame | Parkway AL-6061 frame with round tubes, Bosch motor mount, and rack and fender mounts |
| Fork | Parkway alloy disc fork, 1-1/8" threadless steerer |
| Drivetrain | |
| Crankset | Samox alloy 165mm |
| Chaining | Samox 38t |
| Drive System | Bosch Active Line |
| Rear Derailleur | Shimano Altus |
| Shifters | Shimano Altus 9-speed |
| Chain | KMC e9S EPT Anti-Rust |
| Cassette | Shimano CS-HG200, 11-34t |
| Battery | Bosch PowerPack 400 Performance frame mount |
| Controller | Bosch Purion compact computer |
| Motor | Bosch Active Line 250 watts, up to 40 Nm torque, 20 mph assist |
| Charger | Bosch 2 Amp Compact Charger |
| Components | |
| Brake Levers | Tektro HD-M276 |
| Brakes | Tektro HD-M276 |
| Headset | 1-1/8" threadless |
| Stem | Kalloy AS-901 15° 1-1/8" threadless, 75mm (XS/SM), 90mm (MD/LG) |
| Handlebar | Insert Function Mustache 25.4mm diameter, 595mm (XS/SM), 610mm (MD/LG) width |
| Seatpost | 27.2mm, 300mm length |
| Grips | Synthetic leather 128 mm |
| Saddle | Civia comfort stitched, steel rails |
| Kickstand | Alloy, heavy duty, center mount for ebikes |
| Pedals | Wellgo Neighborhood, alloy with rubber tops |
| Extras | Handlebar water bottle mount |
| Wheels | |
| Wheelset | KT QR hubs, Weinmann Schrader valve 36h rims |
| Tires | Kenda Kwick Roller Sport 26 x 2.0", black with mocha sidewalls with K-Shield |