# **CIVIA Lowry Step-Thru 8-Speed Internal FRAMESHEET**

Civia offers stylish, comfortable, affordable bikes that allow people to discover the joy just around the corner. We believe that riding a bike helps you see the world in a new way, that some of life's best things are found right outside your front door, and that life is more than getting from one place to another. Thanks for buying a Civia.

AWARNING: CYCLING CAN BE DANGEROUS. BICYCLE PRODUCTS SHOULD BE INSTALLED AND SERVICED BY A PROFESSIONAL MECHANIC. NEVER MODIFY YOUR BICYCLE OR ACCESSORIES. READ AND FOLLOW ALL PRODUCT INSTRUCTIONS AND WARNINGS INCLUDING INFORMATION ON THE MANUFACTURER'S WEBSITE. INSPECT YOUR BICYCLE BEFORE EVERY RIDE. ALWAYS WEAR A HELMET.

Additional Product and Safety instructions can be found at www.civiacycles.com/safety

RETAILER: This framesheet MUST BE provided to the end user.

## INTENDED USE



#### CONDITION 1 CITY TREKKING

Our bikes are designed for riding on a paved surface where the tires are always on the ground.

## **GEOMETRY CHART**

Size	X-Small	Small
A. Top Tube Effective	554mm	574mm
B. Seat Tube C-T	470mm	480mm
C. Head Tube Angle	69°	69°
D. Seat Tube Angle	70°	70°
E. Bottom Bracket Drop	50mm	50mm
F. Chainstay Length	425mm	425mm
G. Head Tube Length	175mm	175mm
H. Fork Length	378mm	378mm
I. Fork Offset	45mm	45mm
J. Wheelbase	1016mm	1036mm
K. Stack	560mm	560mm
L. Reach	350mm	370mm
M. Wheel Diameter	640 (26x1.5)	640 (26x1.5)
N. Stand Over	565mm	562mm

## **GENERAL SPECIFICATIONS & COMPATIBILITY**

Frameset				
Frame		Lowry AL-6061 IGH frame with round tubes, botle cage on downtube, rack & fender mounts		
Fork	Lowry, 100% CroMoly, 1" threaded steerer			
Drivetrair	1			
Crankset		3-piece alloy with chainguard		
Bottom Bracket		VP square 68 x 113mm		
Front Derailleur		N/A		
Rear Derailleur		N/A		
Chain		KMC Anti rust chain		
Cassette		20T sprocket for internal hub		
Chainring		44T on 165mm (XS-SM); 46T on 170mmm (MD-XL)		
Compone	nts			
Headset		1" threaded headset		
Brakes		Tektro long reach caliper		
Brake leve	rs	Tektro 4-finger alloy lever		
Grips		Civia 128mm grips		
Stem		1" quill, 17 degree, Ext 80mm (XS-SM); 100mm (MD-XL) length		
Handlebar		Civia, alloy, 25.4mm diameter		
Saddle		Civia stitched; steel rails		
Seatpost		31.6mm; 350mm length		
Pedals		Civia Neighborhood; alloy with rubber tops		
Extras		Kickstand		
Wheels				
Front Hub	Front Hub KT 100mm nut-type hub 36h; silver			
Rear Hub	Rear Hub Shimano Nexus 8-speed internal geared hub			
Rims	Rims KT/Shimano Nexus 8i hubs + Jalco VP20 Rims; Schrader valve, 36h			
Tires		Kenda Kwest 26 x 1.5" (XS-SM); 700c x 38mm (MD-XL)		



<sup>\*</sup>Standover is measured at the top of the top tube, 50mm in front of the bottom bracket center