CIVIA Lowry Step-Thru Single Speed FRAMESHEET

Civia offers stylish, comfortable, affordable bikes that allow people to discover the joy just around the corner. We believe that riding a bike helps you see the world in a new way, that some of life's best things are found right outside your front door, and that life is more than getting from one place to another. Thanks for buying a Civia.

AWARNING: CYCLING CAN BE DANGEROUS. BICYCLE PRODUCTS SHOULD BE INSTALLED AND SERVICED BY A PROFESSIONAL MECHANIC. NEVER MODIFY YOUR BICYCLE OR ACCESSORIES. READ AND FOLLOW ALL PRODUCT INSTRUCTIONS AND WARNINGS INCLUDING INFORMATION ON THE MANUFACTURER'S WEBSITE. INSPECT YOUR BICYCLE BEFORE EVERY RIDE. ALWAYS WEAR A HELMET.

Additional Product and Safety instructions can be found at www.civiacycles.com/safety

RETAILER: This framesheet MUST BE provided to the end user.

INTENDED USE



CONDITION 1 CITY TREKKING

Our bikes are designed for riding on a paved surface where the tires are always on the ground.

GEOMETRY CHART

| Size | X-Small | Small |
|------------------------|--------------|--------------|
| A. Top Tube Effective | 554mm | 574mm |
| B. Seat Tube C-T | 470mm | 480mm |
| C. Head Tube Angle | 69° | 69° |
| D. Seat Tube Angle | 70° | 70° |
| E. Bottom Bracket Drop | 50mm | 50mm |
| F. Chainstay Length | 425mm | 425mm |
| G. Head Tube Length | 175mm | 175mm |
| H. Fork Length | 378mm | 378mm |
| I. Fork Offset | 45mm | 45mm |
| J. Wheelbase | 1016mm | 1036mm |
| K. Stack | 560mm | 560mm |
| L. Reach | 350mm | 370mm |
| M. Wheel Diameter | 640 (26x1.5) | 640 (26x1.5) |
| N. Stand Over | 565mm | 562mm |

GENERAL SPECIFICATIONS & COMPATIBILITY

| Drivetrain | |
|-----------------------|---|
| Crankset | 3-piece alloy 44t with chainguard |
| Bottom Bracket | VP square 68 x 113mm |
| Chain | KMC Z610 silver |
| Cassette | Shimano 20t freewheel |
| Components | |
| Brake Levers | Tektro 4-finger lever |
| Brakes | Tektro long reach caliper |
| Headset | 1" threaded headset |
| Stem | |
| Handlebar | Civia 25.4mm diameter; 570mm (XS-SM); 595mm (MD-XL) width |
| Seatpost | 31.6mm; 350mm length |
| Grips/Tape | Civia 128mm grips |
| Saddle | Civia stitched; steel rails |
| Pedals | Civia Neighborhood; alloy with rubber tops |
| Kickstand | Alloy heavy duty |
| Wheels | |
| Wheelset | KT nut-type hubs; Jalco VP20; Schrader valve; 36h front; 36h rear |
| Tires | Kenda Kwest 26 x 1.5" (XS-SM); 700c x 38mm (MD-XL) |
| Front Hub | KT nut-type 36h; OLD: 100mm |
| Rear Hub | KT nut-type 36h freewheel |
| | |



^{*}Standover is measured at the top of the top tube, 50mm in front of the bottom bracket center