

## CIVIA North Loop eBike 2.0 FRAMESHEET

Civia offers stylish, comfortable, affordable bikes that allow people to discover the joy just around the corner. We believe that riding a bike helps you see the world in a new way, that some of life's best things are found right outside your front door, and that life is more than getting from one place to another. Thanks for buying a Civia.

**⚠WARNING:** CYCLING CAN BE DANGEROUS. BICYCLE PRODUCTS SHOULD BE INSTALLED AND SERVICED BY A PROFESSIONAL MECHANIC. NEVER MODIFY YOUR BICYCLE OR ACCESSORIES. READ AND FOLLOW ALL PRODUCT INSTRUCTIONS AND WARNINGS INCLUDING INFORMATION ON THE MANUFACTURER'S WEBSITE. INSPECT YOUR BICYCLE BEFORE EVERY RIDE. ALWAYS WEAR A HELMET.

Additional Product and Safety instructions can be found at [www.civiacycles.com/safety](http://www.civiacycles.com/safety)

RETAILER: This framesheet MUST BE provided to the end user.

### INTENDED USE



#### CONDITION 1 CITY TREKKING

Our bikes are designed for riding on a paved surface where the tires are always on the ground.

### GEOMETRY CHART

Size	XS	SM
<b>A. Top Tube Effective</b>	505mm	540mm
<b>B. Seat Tube C-T</b>	450mm	500mm
<b>C. Head Tube Angle</b>	70.5°	70.5°
<b>D. Seat Tube Angle</b>	74°	74°
<b>E. Bottom Bracket Drop</b>	50mm	50mm
<b>F. Chainstay Length</b>	440mm	440mm
<b>G. Head Tube Length</b>	120mm	160mm
<b>H. Fork Length</b>	392mm	392mm
<b>I. Fork Offset</b>	45mm	45mm
<b>J. Wheelbase</b>	1007mm	1045mm
<b>K. Stack</b>	518mm	556mm
<b>L. Reach</b>	357mm	381mm
<b>M. Wheel Diameter</b>	651 (26x1.75)	651 (26x1.75)
<b>N. Stand Over</b>	701mm	743mm

\*Stand Over is measured with stock tires (26x1.75 / 650x47). Measurement is taken 50mm in front of the BB center.

## GENERAL SPECIFICATIONS & COMPATIBILITY

Frameset	
<b>Frame</b>	North Loop AL-6061 frame with round tubes, Bosch motor mount, rack & fender mounts
<b>Fork</b>	North Loop alloy disc fork 1-1/8" threadless steerer (XS,SM = 26", MD,LG = 650b)
<b>Controller</b>	Bosch Purion
Drivetrain	
<b>Crankset</b>	Samox alloy 38t x 165mm (XS, SM) 170mm (MD, LG)
<b>Drive System</b>	Bosch Active Line Plus
<b>Rear Derailleur</b>	Shimano RD-M610 10-speed
<b>Shifters</b>	Microshift 10-speed Xpress
<b>Chain</b>	KMC e10
<b>Cassette</b>	Sunrace 10-speed 11-36t
<b>Battery</b>	Powerpack 400
<b>Motor</b>	Bosch Active Line Plus
<b>Charger</b>	2A compact
Components	
<b>Brake Levers</b>	Tektro Vela HD-T290 flat bar
<b>Brakes</b>	Tektro Vela HD-T290 hydraulic disc
<b>Headset</b>	1-1/8" threadless; 3 x 10mm spacers
<b>Stem</b>	Kalloy AS-601, 25.4mm, 7°, 1-1/8" threadless, 70/90mm
<b>Handlebar</b>	Riser, 25.4mm diameter, 40mm rise, 15° sweep, 600mm (XS, SM), 620mm (MD, LG)
<b>Seatpost</b>	27.2mm, 350mm length
<b>Grips</b>	Synthetic leather 128mm, brown
<b>Saddle</b>	Civia comfort stitched, steel rails, brown
<b>Pedals</b>	Wellgo Neighborhood, alloy w/ rubber tops
<b>Kickstand</b>	Alloy, heavy duty, stay mount for ebikes
Wheels	
<b>Wheelset</b>	KT QR disc hubs, Weinmann rims 26" and 650b, Schrader valve, 36h
<b>Tires</b>	Kenda Kwick Jersey 26 x 1.75" (XS, SM) and 650b x 1.75" (MD, LG), K-Shield