

## CIVIA Parkway Step-Thru eBike FRAMESHEET

Civia offers stylish, comfortable, affordable bikes that allow people to discover the joy just around the corner. We believe that riding a bike helps you see the world in a new way, that some of life's best things are found right outside your front door, and that life is more than getting from one place to another. Thanks for buying a Civia.

**⚠WARNING:** CYCLING CAN BE DANGEROUS. BICYCLE PRODUCTS SHOULD BE INSTALLED AND SERVICED BY A PROFESSIONAL MECHANIC. NEVER MODIFY YOUR BICYCLE OR ACCESSORIES. READ AND FOLLOW ALL PRODUCT INSTRUCTIONS AND WARNINGS INCLUDING INFORMATION ON THE MANUFACTURER'S WEBSITE. INSPECT YOUR BICYCLE BEFORE EVERY RIDE. ALWAYS WEAR A HELMET.

Additional Product and Safety instructions can be found at [www.civiacycles.com/safety](http://www.civiacycles.com/safety)

RETAILER: This framesheet MUST BE provided to the end user.

### INTENDED USE



#### CONDITION 1 CITY TREKKING

Our bikes are designed for riding on a paved surface where the tires are always on the ground.

### GEOMETRY CHART

Size	X-Small	Small
<b>A. Top Tube Effective</b>	555mm	575mm
<b>B. Seat Tube C-T</b>	500mm	525mm
<b>C. Head Tube Angle</b>	69°	69°
<b>D. Seat Tube Angle</b>	70°	70°
<b>E. Bottom Bracket Drop</b>	58mm	58mm
<b>F. Chainstay Length</b>	480mm	480mm
<b>G. Head Tube Length</b>	200mm	205mm
<b>H. Fork Length</b>	387mm	387mm
<b>I. Fork Offset</b>	45mm	45mm
<b>J. Wheelbase</b>	1069mm	1089mm
<b>K. Stack</b>	593mm	598mm
<b>L. Reach</b>	339mm	357mm
<b>M. Wheel Diameter</b>	658 (26x2.0)	658 (26x2.0)
<b>N. Stand Over</b>	639mm	636mm

\*Standover is measured 50mm in front of the bottom bracket center and using a 26 x 2.0" tire measuring 658mm in diameter

## GENERAL SPECIFICATIONS & COMPATIBILITY

Frameset	
<b>Frame</b>	Parkway AL-6061 frame with round tubes, Bosch motor mount, rack & fender mounts
<b>Fork</b>	Parkway alloy disc fork 1-1/8" threadless steerer
Drivetrain	
<b>Crankset</b>	Samox alloy 165mm (XS, SM) 170mm (MD, LG) arms
<b>Drive System</b>	Bosch Active Line
<b>Rear Derailleur</b>	Sora RD-R3000 9-speed
<b>Shifters</b>	Microshift 9-speed Xpress
<b>Chain</b>	KMC X9e
<b>Cassette</b>	Sunrace 9-speed 11-32t
<b>Battery</b>	Bosch PowerPack 400 Performance frame mount
<b>Controller</b>	Bosch Purion compact computer
<b>Motor</b>	Bosch Active Line 250 watts, up to 40 Nm torque, 20 mph assist
<b>Charger</b>	Bosch 2 Amp Compact Charger
Components	
<b>Brake Levers</b>	Shimano BL-R550 flat bar brake lever
<b>Brakes</b>	Shimano Sora BR-R317 cable-actuated road disc brakes
<b>Headset</b>	VP-A71 1-1/8" threadless
<b>Stem</b>	Kalloy AS-901 15° 1-1/8" threadless, 75/90mm
<b>Handlebar</b>	Mustache 25.4mm diameter, 570mm (XS, SM), 595mm (MD, LG) width
<b>Seatpost</b>	27.2mm, 350mm length
<b>Grips</b>	Synthetic leather 128 mm
<b>Saddle</b>	Civia comfort stitched, steel rails
<b>Kickstand</b>	Alloy, heavy duty, center mount for ebikes
Wheels	
<b>Wheelset</b>	KT QR hubs, Jalco VP20 Schrader valve 36h rims
<b>Tires</b>	Kenda Kwick Roller Sport 26 x 2.0", black w/ mocha sidewalls w/ K-Shield